

R600T RECLAIMER

FEATURES AND BENEFITS



▼ Optional wireless keypad

Efficient connection to the onboard operator keypad to control all functions of the cleaner and the charge pump

▼ Multipurpose recycling

Two 10-in (25.4-cm) desanders and 16 5-in (12.7-cm) desilters to remove sand and coarse silts prior to the next stage in the cleaning process, resulting in dry solids

▼ Desilter manifold

Ability to minimize turbulence or excessive vacuum for efficient separation of sands and coarse silts

▼ Optimized shaker deck

Long wedge blocks with pry-in/pry-out functionality to speed up installation, maximize G-force and expected screen life

▶ Paddle-style agitators

Ability to reduce settling in the tanks by increasing solid suspension

▶ Power flexibility

Ability to configure the reclaimer with or without a generator set mounted onboard



▶ Common components

Standard pump and motor parts to help reduce inventory, adding to operational efficiencies

▶ Diesel-powered jacking legs

No need to power up the entire system for on-site mobilization prep

▶ 7,729-GAL (29,257.4-L) tank capacity

Thorough three-stage cleaning process using a scalped tank, middle tank and clean tank

▶ 1,100-GPM processing capacity

Optimal size for horizontal directional drilling (HDD) projects in the 600 gpm - 1,100 gpm (2,271.2 L/min - 4,163.9 L/min) range

Visit [vermeer.com](https://www.vermeer.com) to learn more.